

Safety Data Sheet

TIGER COMBO™

SECTION 1. IDENT	IFICATION
Product Identifier	TIGER COMBO™
Other Means of Identification	Sulphur, Sulphate
Recommended Use	Plant nutrient fertilizer.
Restrictions on Use	Always follow safe handling practices.
Manufacturer/Supplier Identifier	Tiger-Sul Products LLC -Hwy 31 West Industrial Park P.O. Box 5; Atmore, AL; 36504, USA., Tiger-Sul Products LLC -61 Stork Rd; Stockton, CA; 95203, USA. Tiger-Sul (Canada) Co, -275137 Range Road 263 P.O. Box 126; Irricana, AB; T0M 1B0, Canada.
Emergency Phone No.	CHEMTREC, (800) 424-9300 -24 hrs Atmore Toll free, (800) 239-3647 Stockton Toll free, (877) 299-3399 Irricana Toll free, (877) 299-3399

SECTION 2. HAZARD IDENTIFICATION

Classified according to Canada's Hazardous Products Regulations (WHMIS 2015) and the US Hazard Communication Standard (HCS 2012).

Classification

Combustible dust - Category 1; Acute toxicity (Dermal) - Category 4; Skin irritation - Category 2; Eye irritation - Category 2A; Skin sensitization - Category 1B; Carcinogenicity - Category 1A Label Elements



May form combustible dust concentrations in air. May cause cancer. Causes skin and eye irritation. May be harmful if swallowed, in contact with skin or if inhaled.

Other Hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixture

Chemical Name	CAS No.	%	Other Identifiers	Other Names
Ammonium sulfate	7783-20-2	55.48 - 62.61	EU EINECS/ELINCS Number:231-984-1	(NH4)2SO4
SULFUR	7704-34-9	35.51 - 37.41	EU EINECS/ELINCS Number:231-722-6	S
BENTONITE	1302-78-9	3.98 - 4.16	EU EINECS/ELINCS Number:215-108-5	CLAY
SILICA QUARTZ	14808-60-7	0.128 - 0.134	EU EINECS/ELINCS Number:238-878-4	SiO2

SECTION 4. FIRST-AID MEASURES

First-aid Measures

Inhalation

Take precautions to ensure your own safety before attempting rescue (e.g. wear appropriate protective equipment). Remove source of exposure or move to fresh air.

Skin Contact

Avoid direct contact. Wear chemical protective clothing if necessary. Take off contaminated clothing, shoes and leather goods (e.g. watchbands, belts). Wash gently and thoroughly with lukewarm, gently flowing water and mild soap for 5 minutes.

Eye Contact

Wear eye protection to avoid dust getting into eyes. If contact and irritation occurs rinse the contaminated eye(s) with lukewarm, gently flowing water for 5 minutes, while holding the eyelid(s) open. Remove contact lenses, if present and easy to do.

First-aid Comments

Get medical advice or attention if you feel unwell or are concerned.

Most Important Symptoms and Effects, Acute and Delayed

If in eyes: may cause moderate to severe irritation. Symptoms include sore, red eyes, and tearing.

If on skin: may cause mild to moderate irritation

If inhaled: repeated or long term inhalation can cause respiratory problems (SILICA, QUARTZ).

Immediate Medical Attention and Special Treatment

Target Organs

None known.

Special Instructions

Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media

Water spray or fog is preferred If water is not available, use Carbon dioxide, dry chemical powder or appropriate foam. Small fires may be smothered with sand.

Unsuitable Extinguishing Media

Avoid scattering spilled material with high pressure water streams.

Specific Hazards Arising from the Product

Combustible dust. Powder may form explosive dust-air mixture.

Special Protective Equipment and Precautions for Fire-fighters

Wear positive pressure self-contained breathing apparatus (SCBA) Structural firefighters' protective clothing will only provide limited protection.

Chemical protective clothing (e.g. chemical splash suit) and positive pressure SCBA may be necessary.

Hydrogen Sulphide is heavier than air and may collect in low lying areas and confined spaces.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment, and Emergency Procedures

Do not touch damaged containers or spilled product unless wearing appropriate protective equipment. Use the personal protective equipment recommended in Section 8 of this safety data sheet.

Environmental Precautions

Prevent uncontrolled release to the environment.

Methods and Materials for Containment and Cleaning Up

Avoid generating dust. Avoid dry sweeping. If necessary, use a dust suppressant such as water. Do not use compressed air for clean-up.

SECTION 7. HANDLING AND STORAGE

Precautions for Safe Handling

Avoid breathing in this product. Avoid repeated or prolonged skin contact. Do not get in eyes.

Conditions for Safe Storage

Store in an area that is: cool, well-ventilated, out of direct sunlight and away from heat and ignition sources.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

	ACGIH	TLV®	OSHA PEL		AIHA WEEL	
Chemical Name	TWA	STEL	TWA	Ceiling	8-hr TWA	TWA
SULFUR	10 mg/m3	N.AV.	15 mg/m3	N.AV	N.AV	N.AV
BENTONITE	1 mg/m3	10 mg/m3	N.AV	N.AV	N.AV	N.AV
SILICA QUARTZ	0.025 mg/m3	N.AV	10 mg/m3	N.AV	N.AV	N.AV

Appropriate Engineering Controls

Do not allow product to accumulate in the air in work or storage areas, or in confined spaces. Use local exhaust ventilation, if general ventilation is not adequate to control amount in the air. Provide eyewash in work area, if contact or splash hazard exists.

Individual Protection Measures

Eye/Face Protection

Wear chemical safety goggles.

Skin Protection

Wear long sleeved clothing and impervious gloves.

Respiratory Protection

For non-routine or emergency situations: wear a NIOSH approved self-contained breathing apparatus (SCBA) or supplied air respirator.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Basic Physical and Chemical Properties				
Appearance	Tan - brown prills. Absorbs moisture from the air. Particle Size: 302			
Odour	Not applicable			
Odour Threshold	Not applicable			
рН	Not available			
Melting Point/Freezing Point	Not applicable (melting); Not applicable (freezing)			
Initial Boiling Point/Range	Not available			
Flash Point	Not available			
Evaporation Rate	Not applicable			
Flammability (solid, gas)	Not applicable			
Upper/Lower Flammability or	0.14% (SULFUR) (upper); 0.0035% (SULFUR) (lower)			
Explosive Limit				
Vapour Pressure	Not applicable			
Vapour Density (air = 1)	Not available			
Relative Density (water = 1)	Not applicable			
Solubility	Moderately soluble in water; Not available (in other liquids)			
Partition Coefficient,	Not applicable			
n-Octanol/Water (Log Kow)				
Auto-ignition Temperature	> 232 ºC (450 ºF) (SULFUR)			
Decomposition Temperature	Not available			
Viscosity	Not applicable (kinematic); Not applicable (dynamic)			
Other Information				
Physical State	Solid			
Bulk Density	59 lb/ft3			
Other Physical Property 2	Combo ground and tested at <75 micron particle size and <5% moisture per			
	ASTM E1226. Kst value 18 bar.m/s; Pmax value 4.6 bar; Rmax value 65 bar/s.			

SECTION 10. STABILITY AND REACTIVITY

Reactivity

Not reactive under normal conditions of use.

Chemical Stability

Normally stable.

Possibility of Hazardous Reactions

None expected under normal conditions of storage and use. Reacts in the presence of high energy sources (e.g. welding arcs). Dust may cause a fire or explosion.

Conditions to Avoid

Reacts with bases to form ammonia Avoid moisture and high humidity; Ammonium Sulphate absorbs water from the air.

Incompatible Materials

Do not store with oxidizers, strong acids or bases. Forms toxic chemicals on contact with: strong bases (e.g. sodium hydroxide).

Hazardous Decomposition Products

Sulphur Dioxide.

SECTION 11. TOXICOLOGICAL INFORMATION

Likely Routes of Exposure

Inhalation; eye contact; skin contact.

Acute Toxicity

Chemical Name	LC50	LD50 (oral)	LD50 (dermal)
SULFUR	> 0.047 mg/L (rat) (4-hour exp)	> 5000 mg/kg (rat)	Not Available
BENTONITE	Not Available	5000 mg/kg (rat)	Not Available
AMMONIUM SULFATE	> 1800 mg/m3 (guinea pig) (4-hr exp)	2840-4250 mg/kg (rat)	> 2000 mg/kg (rat)
SILICA QUARTZ	Not Available	500 mg/kg (rat)	Not Available

Skin Corrosion/Irritation

May cause irritation to skin, eyes and respiratory tract.

Serious Eye Damage/Irritation

Can cause serious eye irritation.

STOT (Specific Target Organ Toxicity) - Single Exposure

Inhalation

Nose and throat irritation.

Skin Absorption

May cause skin to become sensitive to sunlight (ultraviolet light).

Ingestion

May be harmful If large amounts are swallowed symptoms may include nausea, vomiting, stomach cramps and diarrhea.

Aspiration Hazard

Not known to be an aspiration hazard.

STOT (Specific Target Organ Toxicity) - Repeated Exposure

If inhaled: lung injury, irritation of the respiratory system. May cause respiratory tract injury.

Respiratory and/or Skin Sensitization

May cause an allergic reaction (skin sensitization) based on limited evidence.

Carcinogenicity

If inhaled: Known to cause: lung cancer. A1 - Confirmed human carcinogen. (SILICA QUARTZ)

Reproductive Toxicity

Development of OffspringNo information was located.Sexual Function and FertilityNo information was located.Effects on or via LactationNo information was located.

Germ Cell Mutagenicity

No information was located.

Interactive Effects No information was located.

SECTION 12. ECOLOGICAL INFORMATION

Avoid uncontrolled release.

Ecotoxicity

May cause long lasting harmful effects to aquatic life.

Acute Aquatic Toxicity

Chemical Name	LC50 Fish	EC50 Crustacea	ErC50 Aquatic Plants	ErC50 Algae
SULFUR	< 14 mg/L (Lepomis macrochirus (bluegill); 96-hour; fresh water; static)	> 5000 mg/L (Daphnia magna (water flea); 48- hour; fresh water; static)	Not Available	Not Available
BENTONITE	19000 mg/L (Oncorhynchus mykiss (rainbow trout); 96-hour; fresh water; static)	Not Available	Not Available	Not Available

Persistence and Degradability

No ingredient of this product or its degradation products is known to be highly persistent.

Bioaccumulative Potential

This product and its degradation products are not known to bioaccumulate.

Mobility in Soil

If released into the environment, this product is expected to move slowly through the soil, based on physical and chemical properties.

Contamination of groundwater could occur. with uncontrolled release.

Other Adverse Effects

There is no information available.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal Methods

Dispose of contents and container in accordance with local, regional, national and international regulations.

SECTION 14. TRANSPORT INFORMATION

Not regulated under Canadian TDG regulations. Not regulated under US DOT Regulations.

Environmental Hazards	Potential Marine Pollutant (Ammonium sulfate)
Special Precautions	Not applicable

Transport in Bulk According to Annex II of MARPOL 73/78 and the IBC Code Not applicable

SECTION 15. REGULATORY INFORMATION

Safety, Health and Environmental Regulations

Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the SDS contains all of the information required by the Controlled Products Regulations.

Domestic Substances List (DSL) / Non-Domestic Substances List (NDSL)

Listed on the DSL.

USA

Additional USA Regulatory Lists

This product does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and ReauthorIzation Act (SARA) (40 CFR 355).

▲ WARNING: This product can expose you to chemicals including crystalline silica, which is known to the State of California to cause cancer when inhaled. For more information, go to www.P65Warnings.ca.gov.

Listed Pennsylvania Right To Know. (SULFUR). (SILICA QUARTZ)

SECTION 16. OTHER INFORMATION

NFPA Rating	Health - 1	Flammability - 1	Instability - 0
SDS Prepared By Phone No. Date of Preparation Date of Last Revision	Tiger-Sul (877) 299-33 August 22, 20 March 1, 202	017	
Revision Indicators		•	changed on 01/02/2019: Updated California Proposition 65 NCS Numbers. Added Kst, Pmax and Rmax values.
Key to Abbreviations	Safety and H OSHA = US	ealth Occupational Safety a	ssociation NIOSH = National Institute for Occupational and Health Administration of Governmental Industrial Hygienists
Disclaimer	purposes. It i law or regula practice nece sources cons	s not to be construed tion. The user is respo essary safety precautio	solely for information, consideration, and investigation as recommending any practice or product in violation of any onsible to determine the suitability of the material for use and ons. The information presented has been compiled from able and is reliable to the best of our knowledge and is not to ality specification.

