



TIGER HUMIK

SECTION 1. IDENTIFICATION

Product Identifier	TIGER HUMIK
Other Means of Identification	Pastillated Sulphur, Humates 4%
Recommended Use	Plant nutrient fertilizer.
Restrictions on Use	Always follow safe handling practices.
Manufacturer/Supplier Identifier	Tiger-Sul Products LLC -Hwy 31 West Industrial Park P.O. Box 5; Atmore, AL; 36504, USA., Tiger-Sul Products LLC -61 Stork Rd; Stockton, CA; 95203, USA. Tiger-Sul (Canada) Co, -275137 Range Road 263 P.O. Box 126; Irricana, AB; T0M 1B0, Canada.
Emergency Phone No.	CHEMTREC, (800) 424-9300 -24 hrs Atmore Toll free, (800) 239-3647 Irricana Toll free, (877) 299-3399

SECTION 2. HAZARD IDENTIFICATION

Classified according to Canada's Hazardous Products Regulations (WHMIS 2015) and the US Hazard Communication Standard (HCS 2012).

Classification

Combustible dust - Category 1; Acute toxicity (Dermal) - Category 4; Skin irritation - Category 2; Eye irritation - Category 2A; Skin sensitization - Category 1B; Carcinogenicity - Category 1A

Label Elements



Danger

May form combustible dust concentrations in air.
May cause cancer.
Causes skin and eye irritation.
May be harmful if swallowed, in contact with skin or if inhaled.

Other Hazards

None known.

Product Identifier: TIGER HUMIK - Ver. 2
Date of Preparation: April 15, 2023
Date of Last Revision: November 8, 2023

SDS No.: 0055

Page 01 of 08

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixture:

Chemical Name	CAS No.	%	Other Identifiers	Other Names
SULFUR	7704-34-9	84 - 86	EU EINECS/ELINCS Number: 231-722-6	S
BENTONITE	1302-78-9	13 - 15	EU EINECS/ELINCS Number: 215-108-5	CLAY
Humic acids	1415-93-6	4-5		
SILICA, QUARTZ	14808-60-7	0.59 - 0.62	EU EINECS/ELINCS Number: 238-878-4	SiO ₂

SECTION 4. FIRST-AID MEASURES

First-aid Measures

Inhalation

Take precautions to ensure your own safety before attempting rescue (e.g. wear appropriate protective equipment). Remove source of exposure or move to fresh air.

Skin Contact

Avoid direct contact. Wear chemical protective clothing if necessary. Take off contaminated clothing, shoes and leather goods (e.g. watchbands, belts). Wash gently and thoroughly with lukewarm, gently flowing water and mild soap for 5 minutes.

Eye Contact

Wear eye protection to avoid dust getting into eyes. If contact and irritation occurs rinse the contaminated eye(s) with lukewarm, gently flowing water for 5 minutes, while holding the eyelid(s) open. Remove contact lenses, if present and easy to do.

First-aid Comments

Get medical advice or attention if you feel unwell or are concerned.

Most Important Symptoms and Effects, Acute and Delayed

If in eyes: may cause moderate to severe irritation. Symptoms include sore, red eyes, and tearing. If on skin: may cause mild to moderate irritation if inhaled: repeated or long term inhalation can cause respiratory problems (SILICA, QUARTZ).

Immediate Medical Attention and Special Treatment

Target Organs

None known.

Special Instructions

Treat symptomatically.

Product Identifier: TIGER HUMIK - Ver. 2
Date of Preparation: April 15, 2023
Date of Last Revision: November 8, 2023

SDS No.: 0055

Page 02 of 08

SECTION 5. FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media

Water spray or fog is preferred. If water is not available, use Carbon dioxide, dry chemical powder or appropriate foam. Small fires may be smothered with sand.

Unsuitable Extinguishing Media

Avoid scattering spilled material with high pressure water streams.

Specific Hazards Arising from the Product

Flammable solid.

Combustion products include Sulphur Dioxide and Hydrogen Sulphide.

Special Protective Equipment and Precautions for Fire-fighters

Wear positive pressure self-contained breathing apparatus (SCBA). Structural firefighters' protective clothing will only provide limited protection.

Chemical protective clothing (e.g. chemical splash suit) and positive pressure SCBA may be necessary. Hydrogen Sulphide is heavier than air and may collect in low lying areas and confined spaces.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment, and Emergency Procedures

Do not touch damaged containers or spilled product unless wearing appropriate protective equipment. Use the personal protective equipment recommended in Section 8 of this safety data sheet.

Environmental Precautions

Prevent uncontrolled release to the environment.

Methods and Materials for Containment and Cleaning Up

Avoid generating dust. Avoid dry sweeping. If necessary, use a dust suppressant such as water. Do not use compressed air for clean-up.

SECTION 7. HANDLING AND STORAGE

Precautions for Safe Handling

Avoid breathing in this product. Avoid repeated or prolonged skin contact. Do not get in eyes.

Conditions for Safe Storage

Store in an area that is: cool, well-ventilated, out of direct sunlight and away from heat and ignition sources.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

Chemical Name	ACGIH TLV®		OSHA PEL		AIHA WEEL	
	TWA	STEL	TWA	Ceiling	8-hr TWA	TWA
SULFUR	10 mg/m3		15 mg/m3			
BENTONITE	1 mg/m3	10 mg/m3				
SILICA, QUARTZ	0.025 mg/m3		10 mg/m3			

Appropriate Engineering Controls

Do not allow product to accumulate in the air in work or storage areas, or in confined spaces. Use local exhaust ventilation, if general ventilation is not adequate to control amount in the air. Provide eyewash in work area, if contact or splash hazard exists.

Individual Protection Measures

Eye/Face Protection

Wear chemical safety goggles.

Skin Protection

Wear long sleeved clothing and impervious gloves.

Respiratory Protection

For non-routine or emergency situations: wear a NIOSH approved self-contained breathing apparatus (SCBA) or supplied air respirator.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Basic Physical and Chemical Properties

Appearance	Dark grey - black pellets. Particle Size: 280SGN
Odour	Not applicable
Odour Threshold	Not applicable
pH	Not available
Melting Point/Freezing Point	115 °C (239 °F) (SULFUR) (melting); Not applicable (freezing)
Initial Boiling Point/Range	Not applicable
Flash Point	207 °C (405 °F) (closed cup) (SULFUR)
Evaporation Rate	Not applicable
Flammability (solid, gas)	Flammable solid. (SULFUR)
Upper/Lower Flammability or Explosive Limit	0.14% (SULFUR) (upper); 0.0035% (SULFUR) (lower)
Vapour Pressure	Not applicable
Vapour Density (air = 1)	Not applicable
Relative Density (water = 1)	Not applicable
Solubility	Insoluble in water; Not available (in other liquids)
Partition Coefficient, n-Octanol/Water (Log Kow)	Not applicable

Product Identifier: TIGER HUMIK - Ver. 2
Date of Preparation: April 15, 2023
Date of Last Revision: November 8, 2023

SDS No.: 0055

Page 04 of 08

Auto-ignition Temperature	232 °C (450 °F) (SULFUR)
Decomposition Temperature	Not available
Viscosity	Not applicable (kinematic); Not applicable (dynamic)
Other Information	
Physical State	Solid
Bulk Density	68.5 lb/ft ³
Vapour Pressure at 50 deg C	Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity

Not reactive under normal conditions of use.

Chemical Stability

Normally stable.

Possibility of Hazardous Reactions

None expected under normal conditions of storage and use.

Reacts in the presence of high energy sources (e.g. welding arcs). Dust may cause a fire or explosion.

Conditions to Avoid

Open flames, sparks, static discharge, heat and other ignition sources.

Incompatible Materials

Oxidizing agents (e.g. peroxides).

Hazardous Decomposition Products

Sulphur Dioxide hydrogen Sulfide.

SECTION 11. TOXICOLOGICAL INFORMATION

Likely Routes of Exposure

Inhalation; eye contact; skin contact.

Acute Toxicity

Chemical Name	LC50	LD50 (oral)	LD50 (dermal)
SULFUR	> 0.047 mg/L (rat) (4-hour exposure)	> 5000 mg/kg (rat)	
BENTONITE		5000 mg/kg (rat)	
SILICA, QUARTZ		500 mg/kg (rat)	

0% of the mixture consists of ingredients of unknown toxicity

1222 mg/kg Acute Dermal Toxicity Estimate

Skin Corrosion/Irritation

May cause irritation to skin, eyes and respiratory tract.

Serious Eye Damage/Irritation

Can cause serious eye irritation.

STOT (Specific Target Organ Toxicity) - Single Exposure

Inhalation

May cause nose and throat irritation.

Skin Absorption

May cause skin to become sensitive to sunlight (ultraviolet light).

Ingestion

Product Identifier: TIGER HUMIK - Ver. 2

SDS No.: 0055

Date of Preparation: April 15, 2023

Date of Last Revision: November 8, 2023

Page 06 of 08

May be harmful If large amounts are swallowed

Symptoms may include nausea, vomiting, stomach cramps and diarrhea.

STOT (Specific Target Organ Toxicity) - Repeated Exposure

If inhaled: lung injury, irritation of the respiratory system. May cause respiratory tract injury.

N.AV.

Respiratory and/or Skin Sensitization

May cause an allergic reaction (skin sensitization) based on limited evidence.

Carcinogenicity

If inhaled: lung cancer. A1 – Confirmed human carcinogen. (SILICA, QUARTZ)

Reproductive Toxicity

Development of Offspring

No information was located.

Sexual Function and Fertility

No information was located.

Effects on or via Lactation

No information was located.

Germ Cell Mutagenicity

No information was located.

Interactive Effects

No information was located.

No information was located for: Aspiration Hazard

SECTION 12. ECOLOGICAL INFORMATION

Avoid uncontrolled release.

Ecotoxicity

Acute Aquatic Toxicity

Chemical Name	LC50 Fish	EC50 Crustacea	ErC50 Aquatic Plants	ErC50 Algae
SULFUR	< 14 mg/L (Lepomis macrochirus (bluegill); 96-hour; fresh water; static)	> 5000 mg/L (Daphnia magna (water flea); 48-hour; fresh water; static)		
BENTONITE	19000 mg/L (Oncorhynchus mykiss (rainbow trout); 96-hour; fresh water; static)			

Chronic Aquatic Toxicity

Chemical Name	NOEC Fish	EC50 Fish	NOEC Crustacea	EC50 Crustacea
BENTONITE		Not available		

Persistence and Degradability

No ingredient of this product or its degradation products is known to be highly persistent.

Bioaccumulative Potential

This product and its degradation products are not known to bioaccumulate.

Mobility in Soil

If released into the environment, this product is expected to move slowly through the soil, based on physical and chemical properties.

Other Adverse Effects

There is no information available.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal Methods

Dispose of contents and container in accordance with local, regional, national and international regulations.

SECTION 14. TRANSPORT INFORMATION

Not regulated under Canadian TDG regulations. Not regulated under US DOT Regulations.

Environmental Hazards

Not applicable

Special Precautions Not applicable

Transport in Bulk According to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15. REGULATORY INFORMATION

Safety, Health and Environmental Regulations

Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the SDS contains all of the information required by the Controlled Products Regulations.

Domestic Substances List (DSL) / Non-Domestic Substances List (NDSL)

Listed on the DSL.

USA

Toxic Substances Control Act (TSCA) Section 8(b)

All ingredients are listed on the TSCA Inventory.

Additional USA Regulatory Lists

Listed Pennsylvania Right To Know. (SULFUR)

WARNING: This product can expose you to chemicals including crystalline silica, which is known to the State of California to cause cancer when inhaled. For more information, go to www.P65Warnings.ca.gov.

This product does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355).

Product Identifier: TIGER HUMIK - Ver. 2

Date of Preparation: April 15, 2023

Date of Last Revision: November 8, 2023

SDS No.: 0055

Page 08 of 08

SECTION 16. OTHER INFORMATION

NFPA Rating **Health - 1** **Flammability - 1** **Instability - 0**

SDS Prepared By Tiger-Sul

Phone No. (877) 299-3399

Date of Preparation April 15, 2023

Date of Last Revision November 8, 2023

Key to Abbreviations ACGIH® = American Conference of Governmental Industrial Hygienists
NFPA = National Fire Protection Association NIOSH = National Institute for Occupational Safety and Health
OSHA = US Occupational Safety and Health Administration

Disclaimer This Safety Data Sheet is offered solely for information, consideration, and investigation purposes. It is not to be construed as recommending any practice or product in violation of any law or regulation. The user is responsible to determine the suitability of the material for use and practice necessary safety precautions. The information presented has been compiled from sources considered to be dependable and is reliable to the best of our knowledge and is not to be considered as a warranty or quality specification.

Product Identifier: TIGER HUMIK - Ver. 2

SDS No.: 0055

Date of Preparation: April 15, 2023

Date of Last Revision: November 8, 2023

Page 08 of 08